

Metadata Profile for the OASIS Security Assertion Markup Language (SAML)

4 **V1.x**

5 OASIS Standard

1 November 2007

7	Specification URIs:		
8 9	This Version: <pre>http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml1x-metadata-os.html</pre>		
10	http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml1x-metadata-os.odt		
11	http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml1x-metadata-os.pdf		
12 13	Previous Version: http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml1x-metadata-cs-01.html		
14	http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml1x-metadata-cs-01.odt		
15	http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml1x-metadata-cs-01.pdf		
16 17	Latest Version: http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml1x-metadata.html		
18	http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml1x-metadata.odt		
19	http://docs.oasis-open.org/security/saml/Post2.0/sstc-saml1x-metadata.pdf		
20 21	Technical Committee: OASIS Security Services TC		
22 23 24	Chairs: Hal Lockhart, BEA Systems, Inc. Brian Campbell, Ping Identity		
25 26 27	Editors: Greg Whitehead, Hewlett-Packard Company Scott Cantor, Internet2		
28 29	Related Work: This specification supplements the SAML V2.0 metadata specification [SAML2Meta].		
30 31	Declared XML Namespaces(s): urn:oasis:names:tc:SAML:profiles:v1metadata		
32 33 34 35	Abstract: This specification defines a profile of the OASIS SAML V2.0 metadata specification for use ir describing SAML V1.0 and V1.1 entities. Readers should be familiar with the SAML V2.0 metadata specification [SAML2Meta] before reading this document.		

Status: 36 This document was last revised or approved by the SSTC on the above date. The level of 37 approval is also listed above. 38 Technical Committee members should send comments on this specification to the Technical 39 Committee's email list. Others should send comments to the Technical Committee by using the 40 "Send A Comment" button on the Technical Committee's web page at http://www.oasis-41 open.org/committees/security. 42 For information on whether any patents have been disclosed that may be essential to 43 implementing this specification, and any offers of patent licensing terms, please refer to the 44 Intellectual Property Rights section of the Technical Committee web page (http://www.oasis-45 open.org/committees/security/ipr.php. 46

Notices

- Copyright © OASIS Open 2007. All Rights Reserved. 48
- All capitalized terms in the following text have the meanings assigned to them in the OASIS Intellectual 49
- Property Rights Policy (the "OASIS IPR Policy"). The full Policy may be found at the OASIS website. 50
- This document and translations of it may be copied and furnished to others, and derivative works that 51
- comment on or otherwise explain it or assist in its implementation may be prepared, copied, published, 52
- and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice 53
- and this section are included on all such copies and derivative works. However, this document itself may 54
- not be modified in any way, including by removing the copyright notice or references to OASIS, except as 55
- needed for the purpose of developing any document or deliverable produced by an OASIS Technical 56
- Committee (in which case the rules applicable to copyrights, as set forth in the OASIS IPR Policy, must be 57
- followed) or as required to translate it into languages other than English. 58
- The limited permissions granted above are perpetual and will not be revoked by OASIS or its successors 59
- or assigns. 60
- This document and the information contained herein is provided on an "AS IS" basis and OASIS 61
- DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY 62
- WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY 63
- OWNERSHIP RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A 64
- PARTICULAR PURPOSE. 65
- OASIS requests that any OASIS Party or any other party that believes it has patent claims that would 66
- necessarily be infringed by implementations of this OASIS Committee Specification or OASIS Standard, to 67
- notify OASIS TC Administrator and provide an indication of its willingness to grant patent licenses to such 68
- patent claims in a manner consistent with the IPR Mode of the OASIS Technical Committee that produced
- this specification. 70
- OASIS invites any party to contact the OASIS TC Administrator if it is aware of a claim of ownership of any 71
- patent claims that would necessarily be infringed by implementations of this specification by a patent 72
- holder that is not willing to provide a license to such patent claims in a manner consistent with the IPR 73
- Mode of the OASIS Technical Committee that produced this specification. OASIS may include such 74
- claims on its website, but disclaims any obligation to do so. 75
- OASIS takes no position regarding the validity or scope of any intellectual property or other rights that 76
- might be claimed to pertain to the implementation or use of the technology described in this document or 77
- the extent to which any license under such rights might or might not be available; neither does it represent 78
- that it has made any effort to identify any such rights. Information on OASIS' procedures with respect to 79
- 80 rights in any document or deliverable produced by an OASIS Technical Committee can be found on the OASIS website. Copies of claims of rights made available for publication and any assurances of licenses
- 81
- to be made available, or the result of an attempt made to obtain a general license or permission for the 82
- use of such proprietary rights by implementers or users of this OASIS Committee Specification or OASIS 83
- Standard, can be obtained from the OASIS TC Administrator, OASIS makes no representation that any 84
- information or list of intellectual property rights will at any time be complete, or that any claims in such list 85
- are, in fact, Essential Claims. 86
- The name "OASIS" is a trademark of OASIS, the owner and developer of this specification, and should be 87
- used only to refer to the organization and its official outputs. OASIS welcomes reference to, and 88
- implementation and use of, specifications, while reserving the right to enforce its marks against 89
- misleading uses. Please see http://www.oasis-open.org/who/trademark.php for above guidance. 90

91 Table of Contents

92	1 Introduction	5
93	1.1 Notation	5
94	1.2 Normative References	6
95	1.3 Non-Normative References	6
96	2 SAML V1.x Metadata Profile	
97	2.1 Required Information	7
98	2.2 Profile Overview	
99	2.3 Element <md:entitiesdescriptor></md:entitiesdescriptor>	7
100	2.4 Element <md:entitydescriptor></md:entitydescriptor>	7
101	2.5 Element <md:idpssodescriptor></md:idpssodescriptor>	8
102	2.6 Element <md:spssodescriptor></md:spssodescriptor>	9
103	2.7 Element <md:attributeauthoritydescriptor></md:attributeauthoritydescriptor>	10
104	2.8 Element <md:authnauthoritydescriptor></md:authnauthoritydescriptor>	10
105	2.9 Element <md:pdpdescriptor></md:pdpdescriptor>	
106	2.10 Element <md:keydescriptor></md:keydescriptor>	11
107	Appendix A. Acknowledgements	12

1 Introduction

- This specification defines a profile of the SAML V2.0 metadata specification [SAML2Meta] for use in describing SAML V1.0 and V1.1 entities and profiles.
- 111 Unless specifically noted, nothing in this document should be taken to conflict with the SAML V2.0
- metadata specification. Readers are advised to familiarize themselves with that specification first.

1.1 Notation

108

113

121

122

123

124 125

126

127 128

129

- This specification uses normative text to describe the use of SAML V2.0 metadata with SAML V1.0 and V1.1 profiles.
- The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD
- NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this specification are to be interpreted as
- 118 described in [RFC 2119]:
- 119 ...they MUST only be used where it is actually required for interoperation or to limit behavior 120 which has potential for causing harm (e.g., limiting retransmissions)...
 - These keywords are thus capitalized when used to unambiguously specify requirements over protocol and application features and behavior that affect the interoperability and security of implementations. When these words are not capitalized, they are meant in their natural-language sense.

Listings of XML schemas appear like this.

Example code listings appear like this.

Conventional XML namespace prefixes are used throughout the listings in this specification to stand for their respective namespaces as follows, whether or not a namespace declaration is present in the example:

Prefix	XML Namespace	Comments
saml:	urn:oasis:names:tc:SAML:1.0:assertion	This is the SAML V1.0 and V1.1 assertion namespace [SAML11Core].
samlp:	urn:oasis:names:tc:SAML:1.0:protocol	This is the SAML V1.0 and V1.1 protocol namespace [SAML11Core].
saml2:	urn:oasis:names:tc:SAML:2.0:assertion	This is the SAML V2.0 assertion namespace defined in the SAML V2.0 core specification [SAML2Core].
md:	urn:oasis:names:tc:SAML:2.0:metadata	This is the SAML V2.0 metadata namespace defined in the SAML V2.0 metadata specification [SAML2Meta].
saml1md:	urn:oasis:names:tc:SAML:profiles:v1metadata	This is the namespace defined by this document and its accompanying schema [SAML1MD-xsd].
xs:	http://www.w3.org/2001/XMLSchema	This namespace is defined in the W3C XML Schema specification [Schema1]. In schema listings, this is the default namespace and no prefix is shown.

This specification uses the following typographical conventions in text: <SAMLElement>,

130 <ns:ForeignElement>, Attribute, **Datatype**, OtherKeyword.

1.2 Normative References

132 133	[RFC 2119]	S. Bradner. Key words for use in RFCs to Indicate Requirement Levels. IETF RFC 2119, March 1997. See http://www.ietf.org/rfc/rfc2119.txt.
134 135 136 137	[SAML11Bind]	E. Maler et al. <i>Bindings and Profiles for the OASIS Security Assertion Markup Language (SAML) V1.1.</i> OASIS, September 2003. Document ID oasis-sstc-saml-bindings-1.1. See http://www.oasis-open.org/committees/download.php/3405/oasis-sstc-saml-bindings-1.1.pdf.
138 139 140 141	[SAML11Core]	E. Maler et al. Assertions and Protocols for the OASIS Security Assertion Markup Language (SAML) V1.1. OASIS, September 2003. Document ID oasis-sstc-saml-core-1.1. See http://www.oasis-open.org/committees/download.php/3406/oasis-sstc-saml-core-1.1.pdf.
142 143 144	[SAML1MD-xsd]	S.Cantor et al. SAML V1.x metadata schema. OASIS SSTC, July 2006. Document ID sstc-saml1x-metadata. See http://www.oasis-open.org/committees/security/.
145 146 147 148	[SAML2Core]	S. Cantor et al. Assertions and Protocols for the OASIS Security Assertion Markup Language (SAML) V2.0. OASIS Standard, March 2005. Document ID saml-core-2.0-os. See http://docs.oasis-open.org/security/saml/v2.0/saml-core-2.0-os.pdf.
149 150 151	[SAML2Meta]	S. Cantor et al. <i>Metadata for the OASIS Security Assertion Markup Language</i> (<i>SAML</i>) <i>V2.0</i> . OASIS Standard, March 2005. Document ID saml-metadata-2.0-os. See http://docs.oasis-open.org/security/saml/v2.0/saml-metadata-2.0-os.pdf.
152 153 154	[Schema1]	H. S. Thompson et al. <i>XML Schema Part 1: Structures</i> . World Wide Web Consortium Recommendation, May 2001. See http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/.

1.3 Non-Normative References

155

156 157	[SAML2Gloss]	J. Hodges et al. <i>Glossary for the OASIS Security Assertion Markup Language</i> (SAML) V2.0. OASIS Standard, March 2005. Document ID saml-glossary-2.0-os.
158		See http://docs.oasis-open.org/security/saml/v2.0/saml-glossary-2.0-os.pdf.

2 SAML V1.x Metadata Profile

- SAML profiles require agreements between system entities regarding identifiers, binding/profile support
- and endpoints, certificates and keys, and so forth. A metadata specification is useful for describing this
- information in a standardized way.
- Although SAML V1.0 and V1.1 did not include such a specification, SAML V2.0 includes one in
- 164 [SAML2Meta]. This specification profiles the SAML V2.0 metadata specification for use with the
- SAML V1.0 and V1.1-based profiles and exchanges expected between system entities.

2.1 Required Information

- 167 Identification: urn:oasis:names:tc:SAML:profiles:v1metadata
- 168 Contact information: security-services-comment@lists.oasis-open.org
- 169 **Description:** Given below.
- 170 Updates: None

159

166

171

2.2 Profile Overview

- SAML V2.0 metadata describes a system entity by means of the <md:EntityDescriptor> element
- and a set of "roles" supported by the entity. Role elements profiled for use with SAML V1.0 and V1.1
- include <md:IDPSSODescriptor>, <md:SPSSODescriptor>,
- 175 <md:AttributeAuthorityDescriptor>, <md:AuthnAuthorityDescriptor>, and
- 176 <md: PDPDescriptor>. Specific use of these elements MUST adhere to the profile outlined in the
- 177 following sections.
- 178 The SAML V2.0 roles of identity provider (IdP) and service provider (SP) correspond to the roles
- described in the SAML V1.0 and V1.1 specifications as "source site" and "destination site". This
- specification adopts the SAML V2.0 terminology [SAML2Gloss].
- 181 SAML V2.0 metadata uses a protocol Support Enumeration attribute on each role element, the value
- of which is a list of protocol URIs, to indicate which protocols are supported by an entity in a role.
- SAML V2.0 metadata specifies the use of the SAML V2.0 protocol namespace URI to indicate support for
- 184 SAML V2.0. Since SAML V1.0 and V1.1 both use the same XML protocol namespace URI,
- 185 urn:oasis:names:tc:SAML:1.0:protocol, this convention is not adequate to distinguish between
- support for SAML V1.0 and V1.1.
- For this reason, we define distinct values for use in identifying SAML V1.0 or V1.1 protocol support: the
- original value of urn:oasis:names:tc:SAML:1.0:protocol and a new value of
- 189 urn:oasis:names:tc:SAML:1.1:protocol respectively.

2.3 Element <md:EntitiesDescriptor>

- 191 This element is used as described in [SAML2Meta]. Multiple entities can be collected into groups using
- 192 this element.

190

193

2.4 Element <md:EntityDescriptor>

- 194 A SAML V1.x identity or service provider SHOULD be represented by exactly one
- 195 <md:EntityDescriptor>. Its unique identifier MUST be placed in the entityID XML attribute. It is

- RECOMMENDED that this identifier follow the rules for SAML V2.0 "entity" identifiers, as described in 196 section 8.3.6 of [SAML2Core]. 197
- In the case of an identity provider, the entityID MUST match the Issuer attribute that the identity 198
- 199 provider includes in the assertions that it generates. In the case of a service provider, the entityID
- 200 MUST be the <saml: Audience> value that the service provider associates with itself (such as would be
- used in assertions that contain a <saml: AudienceRestrictionCondition>). 201
- The schema definition for the entityID XML attribute requires that the value be a URI of no more than 202
- 1024 characters in length. Therefore, only SAML V1.x entities able to identify themselves in this fashion 203
- are able to use this profile. 204
- 205 For the purposes of SAML V1.x, only use of the <md:IDPSSODescriptor>, <md:SPSSODescriptor>,
- <md:AttributeAuthorityDescriptor>, <md:AuthnAuthorityDescriptor>, and 206
- <md: PDPDescriptor> elements is defined by this profile. 207
- 208 Use of the <md:RoleDescriptor> abstract element with an xsi:type derived from
- md:RoleDescriptorType is undefined by this profile, but MAY be defined elsewhere as appropriate;
- usage of the protocol Support Enumeration attribute SHOULD be consistent with this profile when 210
- used with SAML V1.x entities. 211

215

- The use of the <md: AffiliationDescriptor> element is also undefined by this profile, as the
- affiliation concept was introduced with SAML V2.0. 213
- In other respects, this element is used as described in [SAML2Meta].

2.5 Element <md:IDPSSODescriptor>

- A SAML V1.x identity provider MUST include this element in its metadata. The 216
- protocolSupportEnumeration XML attribute MUST include at least one of the following values:

```
urn:oasis:names:tc:SAML:1.0:protocol urn:oasis:names:tc:SAML:
218
           1.1:protocol
219
```

- For identity providers that support the SAML V1.x Browser/Artifact profile and the mandatory type 0x0001 220 artifact format [SAML11Bind], it is RECOMMENDED that the SHA-1 hash of their entityID be used as 221
- their SourceID when constructing artifacts. 222
- SAML V1.x identity providers that do not use the SHA-1 hash of their entityID as their SourceID 223
- MUST include a <saml1md: SourceID> element containing the hex-encoded value of their 20-byte 224
- SourceID in the <Extensions> element of their <md: IDPSSODescriptor>. 225
- The schema [SAML1MD-xsd] for the <saml1md:SourceID> element is as follows: 226

```
227
            <schema
228
                targetNamespace="urn:oasis:names:tc:SAML:profiles:v1metadata"
229
                xmlns:saml1md="urn:oasis:names:tc:SAML:profiles:v1metadata"
230
                xmlns="http://www.w3.org/2001/XMLSchema"
                elementFormDefault="unqualified"
231
                attributeFormDefault="ungualified"
232
233
                blockDefault="substitution"
                version="1.0">
234
                <annotation>
235
236
                    <documentation>
237
                         Document identifier: sstc-samllx-metadata
238
                         Location: http://www.oasis-open.org/committees/documents.php?
239
            wg abbrev=security
240
                         Revision history:
241
                         V1.0 (March 2005):
242
                           Initial version.
243
                    </documentation>
244
                </annotation>
                <element name="SourceID">
245
```

Neither SAML V1.0 nor SAML V1.1 defines a protocol for initiating single sign-on at a service provider.

- 254 Accordingly, this specification does not define any Binding URIs for use with the
- 255 <md:SingleSignOnService> element. SAML V1.x identity providers MAY include a
- 256 <md:SingleSignOnService> element with a Binding attribute that refers to a single sign-on request
- 257 profile defined elsewhere. The WantAuthnRequestsSigned XML attribute MAY be used if it is
- 258 applicable to the request profile in question.
- Likewise, neither SAML V1.0 nor 1.1 defines a protocol for single logout. Accordingly, this specification
- does not define any Binding URIs for use with the <md:SingleLogoutService> element.
- 261 SAML V1.x identity providers MAY include a <md:SingleLogoutService> element with a Binding
- 262 attribute that refers to a single logout profile defined elsewhere.
- 263 The <md:ArtifactResolutionService> endpoint element is defined for use specifically in support of
- the SAML V1.x Browser/Artifact profile [SAML11Bind]. This is analogous but not identical to its purpose in
- ²⁶⁵ [SAML2Meta]. In particular, SAML V2.0 artifacts are NOT the same as or interchangeable with SAML V1.x
- artifacts and CANNOT be used in the SAML V1.x Browser/Artifact profile.
- 267 Related to this, the index XML attribute on these elements, while required by the schema, cannot be
- used within the SAML V1.x Browser/Artifact profile and its use is undefined. That is, artifacts in SAML V1.x
- are not indexed by endpoint. All endpoints are assumed to be equivalent and MUST share state so as to
- 270 have the ability to resolve any artifact issued by the identity provider.
- 271 The SAML V2.0 < saml 2: Attribute > element (which can appear in this element) MAY be used to
- document support for particular SAML V1.x attributes and values. By convention, the NameFormat and
- 273 Name XML attributes MUST be used to represent the SAML V1.x AttributeNamespace and
- 274 AttributeName XML attributes, respectively. Any other XML attributes, such as FriendlyName, MAY
- be present but are ignored for the purposes of identifying the corresponding SAML V1.x attribute.
- 276 Use of the <md:ManageNameIDService> and <md:NameIDMappingService> endpoint elements is
- 277 undefined.

279

278 In other respects, this element is used as described in [SAML2Meta].

2.6 Element <md:SPSSODescriptor>

- 280 A SAML V1.x service provider MUST include this element in its metadata. The
- 281 protocolSupportEnumeration XML attribute MUST include at least one of the following values:

```
urn:oasis:names:tc:SAML:1.0:protocol urn:oasis:names:tc:SAML:
1.1:protocol
```

- The <md: AssertionConsumerService > element's Binding XML attribute MUST contain the value
- 285 urn:oasis:names:tc:SAML:1.0:profiles:browser-post to indicate support for the SAML V1.x
- 286 Browser/POST profile, or urn:oasis:names:tc:SAML:1.0:profiles:artifact-01 to indicate
- support for the SAML V1.x Browser/Artifact profile [SAML11Bind].
- 288 Related to this, the use of the index XML attribute on these elements, while required by the schema,
- cannot be referenced within the SAML V1.x Browser/Artifact or Browser/POST profiles and its use is
- 290 undefined.
- The AuthnRequestsSigned XML attribute MAY be used if it is applicable to a request profile outside the
- scope of the SAML V1.x specifications but supported by the service provider.
- 293 The <md: RequestedAttribute> element (which can appear within the optional

- 294 <md:AttributeConsumingService> child element) MAY be used to document requirements for
- particular SAML V1.x attributes and values. By convention, the NameFormat and Name XML attributes
- 296 MUST be used to represent the SAML V1.x AttributeNamespace and AttributeName XML
- 297 attributes, respectively. Any other XML attributes, such as FriendlyName, MAY be present but are
- 298 ignored for the purposes of identifying the corresponding SAML V1.x attribute.
- 299 As with the <md:AssertionConsumerService> element, the use of the index XML attribute on the
- 300 <md:AttributeConsumingService> element is required by the schema, but it cannot be referenced
- within the SAML V1.x Browser profiles and its use is undefined. As a consequence, the use of multiple
- 302 <md:AttributeConsumingService> elements within a single parent element is also undefined.
- Neither SAML V1.0 nor V1.1 defines a protocol for single logout. Accordingly, this specification does not
- define any Binding URIs for use with the <md: SingleLogoutService> element. SAML V1.x service
- providers MAY include a <md:SingleLogoutService> element with a Binding attribute that refers to
- a single logout profile defined elsewhere.
- 307 Use of the <md:ManageNameIDService> and <md:ArtifactResolutionService> endpoint
- 308 elements are undefined.

310

322

330

In other respects, this element is used as described in [SAML2Meta].

2.7 Element <md:AttributeAuthorityDescriptor>

- 311 A SAML V1.x attribute authority MUST include this element in its metadata. The
 - protocolSupportEnumeration XML attribute MUST include at least one of the following values:

- The SAML V2.0 < saml2: Attribute > element (which can appear in this element) MAY be used to
- document support for particular SAML V1.x attributes and values. By convention, the NameFormat and
- 317 Name XML attributes MUST be used to represent the SAML V1.x AttributeNamespace and
- 318 AttributeName XML attributes, respectively.
- In other respects, this element is used as described in [SAML2Meta].
- 320 Note that in most cases, the Binding attribute of the endpoints published within this element will have the
- 321 value urn:oasis:names:tc:SAML:1.0:bindings:SOAP-binding.

2.8 Element <md:AuthnAuthorityDescriptor>

- 323 A SAML V1.x authentication authority MUST include this element in its metadata. The
- 324 protocolSupportEnumeration XML attribute MUST include at least one of the following values:

```
325      urn:oasis:names:tc:SAML:1.0:protocol
326      urn:oasis:names:tc:SAML:1.1:protocol
```

- In other respects, this element is used as described in [SAML2Meta].
- Note that in most cases, the Binding attribute of the endpoints published within this element will have the
- 329 value urn:oasis:names:tc:SAML:1.0:bindings:SOAP-binding.

2.9 Element <md:PDPDescriptor>

- 331 A SAML V1.x policy decision point MUST include this element in its metadata. The
- 332 protocolSupportEnumeration XML attribute MUST include at least one of the following values:
- urn:oasis:names:tc:SAML:1.0:protocol urn:oasis:names:tc:SAML:

334 1.1:protocol

338

- In other respects, this element is used as described in [SAML2Meta].
- Note that in most cases, the Binding attribute of the endpoints published within this element will have the
- 337 value urn:oasis:names:tc:SAML:1.0:bindings:SOAP-binding.

2.10 Element <md:KeyDescriptor>

- The <md: KeyDescriptor> element is supported by this profile for the purpose of documenting the
- public key(s) used by an entity to secure SAML V1.x profiles and bindings. Because the use of encryption
- is not defined by SAML V1.x, use of the <md: EncryptionMethod> element and the use XML attribute
- value of encryption are also undefined.
- In other respects, this element is used as described in [SAML2Meta].

Appendix A. Acknowledgements

- The editors would like to acknowledge the contributions of the OASIS Security Services Technical Committee, whose voting members at the time of publication were:
- Hal Lockhart, BEA Systems, Inc.
- Steve Anderson, BMC Software
- Rob Philpott, EMC Corporation
 - Carolina Canales-Valenzuela, Ericsson
- Dana Kaufman, Forum Systems
- Ashish Patel, France Telecom
- Greg Whitehead, Hewlett-Packard Company
- Heather Hinton, IBM

350

355

362

365

367

- Anthony Nadalin, IBM
- Conor P. Cahill, Intel
- Scott Cantor, Internet2
- Bob Morgan, Internet2
- Tom Scavo, National Center for Supercomputing Applications
- Peter Davis, NeuStar
- Jeff Hodges, NeuStar
 - Frederick Hirsch, Nokia
- Abbie Barbir, Nortel
- Paul Madsen, NTT Corporation
 - Ari Kermaier, Oracle
- Prateek Mishra, Oracle
 - Brian Campbell, Ping Identity
- Bhavna Bhatnagar, Sun Microsystems
- Eve Maler, Sun Microsystems
- Emily Xu, Sun Microsystems
- David Staggs, Veteran's Health Administration